

MODULAR SELF SERVE CARWASH EQUIPMENT

COMPACT, INNOVATIVE, ENERGY EFFICIENT & EASY TO MAINTAIN



HIGH PRESSURE FRAME WITH ELECTRICAL CABINET

- Available 2-6 bays

- Three phase power loss protection

- CAT 5CP2150 direct drive pump

- 3HP 3 phase motor

- KIP multi-station soap/wax solenoids

- DEMA stainless steel multi-station Spot Free solenoids

- All stainless steel construction; including water manifolds and electrical cabinet

- Low water pressure protection to prevent pumps running dry

Wash Functions

- High Pressure Rinse
- High Pressure Soap (hot)
- High Pressure Wax (hot)
- Spot Free Delivery

LOW PRESSURE FRAME WITH CHEMICAL TANKS

- Hydrominder valves

- Flojet Kalrez® air pumps

- KIP multi-station delivery solenoids

- Flojet air cut-off system

- SMC air regulator with filter

- All stainless steel construction; including water manifolds and electrical cabinet

Wash Functions

- Tyre Cleaner
- Presoak
- Foam Brush
- Tri-colour Splatter Wax

BENEFITS OVER OUR EXISTING MODEL

- Direct drive CAT 5CP pumps are easier to maintain and can run at higher pressure than CAT 310 pump

- No Generant regulator and soap injector to setup and maintain

- CAT pumps have constant water on the inlet to prevent them from running dry and damaging seals (Added safety feature)

- All relays have LED indicators (Added fault finding)

DEVELOPED BY CARWASH OWNERS, FOR CARWASH OWNERS.

SPECIFICATIONS

Equipment	Weight	Dimensions	Water Supply	Power Supply
2 – 3 Bay High Pressure	390 kg	1190 mm W x 1900 mm T x 820 mm D	45 lpm @ 50 psi	32 amp 3 Phase and Neutral
4 – 6 Bay High Pressure	520 kg	1520 mm W x 1900 mm T x 820 mm D	90 lpm @ 50 psi	50 amp 3 Phase and Neutral
2 – 6 Bay Low Pressure	190 kg	1170 mm W x 1760 mm T x 600 mm D	15 lpm @ 50 psi	

* AUS electrical components

TOUCH SELECT BAY CONTROLLER

Carwash Operator Features

Check coin and car counts per bay and reset counters via P.I.N. access

Bay wash down function, allowing 5 minutes of High Pressure Rinse via P.I.N. access

Programming of time can be done in increments of 5 seconds

Customer Features

Microcoin® QL coin acceptor accepts \$1, \$2 coins and multiple tokens

CT400 contactless payment optional

Advanced push button technology for easy selection of wash functions

10 second alert when there is 1 minute remaining on the timer

Time doesn't start counting down until the first selection is made by the customer

Safety Features

Concealed 'hidden shackle' American Lock® with one key access for all wash bays

Coin vault holds an average of \$1200 coins to avoid frequent unauthorised access

Water resistant cover on internal components to decrease possible water damage

Solid state relays incorporated to prevent time accumulation from impact



Optional CT400 contactless payment device

The cash free payment solution your customers are looking for

Convenient, easy to use and reliable

Tap & Wash, it's that easy

Waterproof IP66 standards to withstand the carwash environment



Prowash Australia
13-15 Flight Drive
Tullamarine Victoria 3043
T +61 3 8340 3200
prowash.com.au

Proudly distributed by: